



XHD™ RAC® SwitchTip™

High-Pressure Airless Spray Tip



Improve spraying productivity and reduce downtime with the XHD RAC SwitchTip

- Saves time – no screwdriver required
- Change tip sizes in seconds – without removing the tip guard housing
- Locking tab ensures tip stays securely in guard
- For heavy-duty applications up to 500 bar (50.0 MPa, 7250 psi)
- Recommended for Graco Airless Sprayers and XTR™ Airless Spray Guns

PROVEN QUALITY. LEADING TECHNOLOGY.



XHD RAC SwitchTip

Your best choice for spraying high-pressure coatings

Graco XTR Guns

Rugged design to handle
the toughest protective coatings

Compact design

- Lightweight and ergonomic
- XTR-5:
345 bar (34.5 MPa, 5000 psi)
- XTR-7:
500 bar (50.0 MPa, 7250 psi)
- Variety of handle
and trigger options



XTR-5 Airless Spray Gun

Maximum working pressure:
345 bar (34.5 MPa, 5000 psi)

- XTR500 25 mm round handle,
four-finger trigger, no tip
- XTR501 25 mm round handle,
four-finger trigger, flat tip*
- XTR502 Oval insulated handle,
four-finger trigger, XHD RAC tip*
- XTR503 Oval insulated handle,
two-finger trigger, XHD RAC tip*
- XTR504 25 mm round handle,
four-finger trigger, XHD RAC tip*
- XTR505 25 mm round handle,
two-finger trigger, XHD RAC tip*

XTR-7 Airless Spray Gun

Maximum working pressure:
500 bar (50.0 MPa, 7250 psi)

- XTR700 25 mm round handle,
four-finger trigger, no tip
- XTR701 25 mm round handle,
four-finger trigger, flat tip*
- XTR702 Oval insulated handle,
four-finger trigger, XHD RAC tip*
- XTR703 Oval insulated handle,
two-finger trigger, XHD RAC tip*
- XTR704 25 mm round handle,
four-finger trigger, XHD RAC tip*
- XTR705 25 mm round handle,
two-finger trigger, XHD RAC tip*

* Includes 519 tip



The original reversible high-pressure spray tip,
proudly manufactured by Graco!

		ORIFICE SIZE - INCHES																		
		(MM)	IN	.007	.009	.011	.013	.015	.017	.019	.021	.023	.025	.027	.029	.031	.033	.035	.037	.039
FAN WIDTH	(51-102)	2-4	107	109	111	113	115	117	119	121			225	227	229	231		235		139
	(102-152)	4-6		209	211	213	215	217	219	221								235		239
	(152-203)	6-8	307	309	311	313	315	317	319	321	323	325	327	329	331	333	335	337	339	
	(203-254)	8-10		409	411	413	415	417	419	421	423	425	427	429	431	433	435	437	439	
	(254-305)	10-12		509	511	513	515	517	519	521	523	525	527	529	531	533	535	537	539	
	(305-356)	12-14		609	611	613	615	617	619	621	623	625	627	629	631	633	635	637	639	
	(356-406)	14-16			711	713	715	717	719	721	723	725	727	729	731	733	735	737	739	
	(406-457)	16-18				813	815	817	819	821	823	825	827	829	831	833	835	837	839	
	(457-508)	18-20									923		927		931	933	935	937	939	
	Flow Rate (gpm)		.05	.09	.12	.18	.24	.31	.38	.47	.57	.67	.74	.90	1.03	1.17	1.31	1.47	1.63	
Flow Rate (lpm)		.20	.33	.49	.69	.91	1.17	1.47	1.79	2.15	2.54	2.96	3.42	3.90	4.42	4.98	5.56	6.18		

		ORIFICE SIZE - INCHES																			
		(MM)	IN	.041	.043	.045	.047	.049	.051	.053	.055	.057	.059	.061	.063	.065	.067	.069	.071	.075	.081
FAN WIDTH	(51-102)	2-4																			
	(102-152)	4-6																			
	(152-203)	6-8	341	343	345	347		351		355											
	(203-254)	8-10	441	443	445	447	449	451		455		459	461	463	465	467		471	475	481	
	(254-305)	10-12	541	543	545	547	549	551	553	555	557		561		565	567		571	575		
	(305-356)	12-14	641	643	645	647	649	651		655	657	659	661	663	665	667	669	671	675		
	(356-406)	14-16	741	743		747	749	751	753	755			761		767		771				
	(406-457)	16-18	841	843		847		851		855			861	863		867					
	(457-508)	18-20																			
	Flow Rate (gpm)		1.8	1.98	2.17	2.37	2.58	2.79	4.26	3.25	3.49	3.74	4.0	4.26	4.53	4.82	5.11	5.41	6.04	7.04	
Flow Rate (lpm)		6.83	7.51	8.23	8.98	9.76	10.57	16.13	12.29	13.20	14.14	15.12	16.13	17.17	18.24	19.34	20.48	22.85	26.66		

Water @ 138 bar (13.8 MPa, 2000 psi) - paints with a higher viscosity will decrease the flow rate
Example: for a tip with a .039" orifice and a 254 mm (10") pattern, order XHD539

Graco XHD Guard

XHD001 XHD RAC Guard 7/8" for pressures up to 500 bar (50.0 MPa, 7250 psi)

XHD005 XHD RAC Guard 11/16" for pressures up to 500 bar (50.0 MPa, 7250 psi)

GRACO DISTRIBUTION BVBA Industrieterrein Oude Bunders
Slakweidestraat 31 • B-3630 Maasmechelen
Tel: +32 (89) 770 700 • Fax: +32 (89) 770 777
http://www.graco.com

©2008 Graco Inc. Form No. 339360ENEU Rev. C 02/18 All other brand names or marks are used for identification purposes and are trademarks of their respective owners. All written and visual data contained in this document are based on the latest product information available at the time of publication. Graco reserves the right to make changes at any time without notice.