

### DYNA-LUBE

#### NON-FLAMMABLE FLUID FOR STORAGE IN SPRAYING EQUIPMENT

Dyna-Lube is a companion product to Dynaloy's safety solvents for urethanes. It is non-chlorinated, non-flammable, non-carcinogenic, and non-ozone depleting. Dyna-Lube is used as a storage fluid. After use, polyurethane spray equipment is typically flushed with a cleaning solvent. If the equipment is going to be stored for an extended period of time, a fluid must be introduced into the equipment and through the spray lines. This helps eliminate formation of polyureas and crystallized isocyanates that may form when any remaining residue reacts with moisture in the air.

#### TYPICAL PROPERTIES:

Color	Clear
Specific Gravity	0.86
Flash Point	425°F
Vapor Pressure @25°C	<0.01mm Hg

#### APPLICATION/ DIRECTIONS FOR USE:

##### Spray Unit Storage:

1. Flush the unit thoroughly with Dynasolve CU-6 or Dynaflush to remove most uncured and cured polyurethane.
2. Flush the unit with Dyna-Lube 1-3 times to remove the Dynasolve flushing solvent.
3. Pump Dyna-Lube into the system so that it remains in all areas of the unit.
4. Store unit indefinitely, preferably in a cool, dry place.
5. When starting up to unit, the Dyna-Lube can be flushed out with Dynasolve Iso-Neutralizer. This step is not necessary. The polyurethane can simply be introduced to the unit. The first few pounds of polyurethane sprayed through the machine should be scrapped to avoid any adhesive failures. Note: Dyna-Lube will absorb moisture when left open to the atmosphere so keep container closed when not in use.

#### CAUTION:

Do not take internally. Avoid contact with skin and eyes. Keep away from heat and flame. Wear gloves and safety goggles. Use with adequate ventilation. Please refer to MSDS before use or disposal.

#### AVAILABILITY AND TERMS:

Dyna-Lube is packaged in 5-gallon pails and 55-gallon drums. It is a stock item and can be shipped by UPS (ground or air), truck or air freight. Prices are subject to change without notice.