



## COMPLETE LINE OF MIXERS FOR ALL YOUR REQUIREMENTS!

- Our most popular pneumatic mixer.
- Features a new low noise muffler, coupled with a 1.5 HP air motor.
- Minimal maintenance required.
- Operating speed of ~200 to 1000 RPM max.
- Speed control is on the outlet side allowing maximum power at all times.
- All wetted parts are Stainless Steel
- Collapsible blades allow insertion in to 2" bung holes.
- Drum length mixer is standard, tote length also available.
- Extremely reliable, built to last for years of continuous use.
- Average drum mix time about 20-25 minutes.



DM-101



DME-101

- The IPM mixer line-up now includes an electric version of the popular pneumatic mixer.
- Variable speed from 0 ~ 700 RPM
- Able to handle viscosities exceeding 2500 mPas/cPs.
- Fully enclosed ¾ HP DC motor, much safer than AC versions.
- 7.2 foot lbs. torque generated with standard gear reduction.
- Wetted parts are stainless, comes standard with 8" diameter blades, 13" diameter blades for tote applications also available (fits through 2" bung).
- Comes complete with Dart® speed controller.

- Our latest offering in the drum mixer lineup.
- Features a 1.6:1 gear reduction attachment that allows heavier viscosities to be mixed- in excess of ~2500 mPas/cPs.
- Mixer shown with 13" diameter blades, which collapse to fit through 2" bung holes. Optional 6" adapter to fit large tote holes also available. Optional drum length shaft and blades (8") also available.
- Same low maintenance 1.5 HP air motor as the DM-101.
- Light-weight design ensures ease of use- shipping weight approximately 25 lbs.
- Operating speed 125 ~ 700 RPM, depending on air pressure.
- All aluminum gear box features steel gears for long life.



DMR-101

IPM  
International Pump Manufacturing  
3107 142<sup>nd</sup> Avenue East Suite #106  
Sumner, WA. 98390

Tel: 253-863-2222 Fax: 253-863-2223 Web: [www.ipmpumps.com](http://www.ipmpumps.com) Email: [pwright@ipmpumps.com](mailto:pwright@ipmpumps.com)